



# Standard Hollow Tine - .750MT x 5.500L x .520OD R523472



## Details

Designed to remove a soil core, R&R Standard Hollow Tines are constructed from case hardened tubular steel and are the most economical tines available. Case hardening hardens the inner and outer surfaces of the tine wall to over RC55 for added wear.

## Replaces

|              |                                  |
|--------------|----------------------------------|
| John Deere   | TCU17450                         |
| R&R Products | R100-3634, RMT2965,<br>RTCU17450 |
| Toro         | 100-3634                         |

## Specifications

|                                     |                  |
|-------------------------------------|------------------|
| Manufacturer                        | R&R Products     |
| A - Tine Type                       | Standard Hollow  |
| B - Tine Mounting<br>Dia.           | .750 in (19mm)   |
| C - Tine Length                     | 5.500 in (140mm) |
| D - Tine Tip Outside<br>(Hole) Dia. | .520 in (13.2mm) |
| E - Tine Tip Inside<br>(Core) Dia.  | .400 in (10.2mm) |
| F - Tine Wall<br>Thickness          | .049 in (1.2mm)  |

## Fits Models

John Deere Aercore 1000  
John Deere Aercore 1500  
John Deere Aercore 2000  
John Deere Aercore 800  
Ryan GA30  
Toro ProCore 440  
Toro ProCore 648

## TURF MACHINERY SPARES LTD

3a Monument Way West Woking, GU21 5EN  
01483 764467

<https://turfmachinery.rrproducts.com/>



**Standard Hollow Tine - .750MT x 5.500L**  
**x .520OD**  
R523472



Toro ProCore 660  
Toro ProCore 880  
Toro ProCore 648s

**TURF MACHINERY SPARES LTD**

3a Monument Way West Woking, GU21 5EN  
01483 764467

<https://turfmachinery.rrproducts.com/>