


Alloy Hollow Tine - .750MT x 5.750L x .660OD





Details

Like Standard Hollow Tines, this tine is also tubular and designed to remove a soil core, but they are constructed from a special high carbon alloy steel. The steel tubing is specially manufactured for R&R to achieve uniform hardness of RC45-48 throughout the tine for excellent wear and toughness. These tines are much tougher and resist bending in extremely hard or rocky soils and you can expect 3-4 times longer life than from the Standard Hollow Tines.

Replaces

Toro 108-9134

Specifications

Manufacturer R&R Products
A - Tine Type Alloy Hollow
B - Tine Mounting .750 in (19mm)

Dia.

C - Tine Length 5.75 in (146mm) D - Tine Tip Outside .660 in (16.8mm)

(Hole) Dia.

E - Tine Tip Inside .500 in (12.7mm)

(Core) Dia.

F - Tine Wall .058 in (1.5mm)

Thickness

Fits Models

Toro Fairway Aerator

Toro ProCore 1298

Toro ProCore 440

Toro ProCore 648

Toro ProCore 660

Toro ProCore 864

Toro ProCore 880

TURF MACHINERY SPARES LTD

3a Monument Way West Woking, GU21 5EN 01483 764467

https://turfmachinery.rrproducts.com/



R108-9134

Alloy Hollow Tine - .750MT x 5.750L x .660OD



Toro ProCore 648s

TURF MACHINERY SPARES LTD

3a Monument Way West Woking, GU21 5EN 01483 764467

https://turfmachinery.rrproducts.com/