



# Alloy Hollow Side-Eject Tine - .750MT x 4.750L x .470OD R108-9159



## Details

Manufactured from special high-carbon alloy tubular steel with a precision machined slot in the side wall to allow for more efficient core removal in heavy soils. R&R's unique method of machining maintains the maximum side wall height for strength to avoid bending. These tines are through hardened to RC45-48 to create a much tougher and more wear-resistant tine.

## Replaces

Toro 108-9159

## Specifications

Manufacturer	R&R Products
A - Tine Type	Alloy Hollow Side-Eject
B - Tine Mounting Dia.	.750 in (19mm)
C - Tine Length	4.75 in (121mm)
D - Tine Tip Outside (Hole) Dia.	.470 in (11.9mm)
E - Tine Tip Inside (Core) Dia.	.300 in (7.6mm)
F - Tine Wall Thickness	.058 in (1.5mm)

## Fits Models

Toro Fairway Aerator  
Toro ProCore 1298  
Toro ProCore 440  
Toro ProCore 648  
Toro ProCore 660  
Toro ProCore 864  
Toro ProCore 880  
Toro ProCore 648s

## TURF MACHINERY SPARES LTD

3a Monument Way West Woking, GU21 5EN  
01483 764467

<https://turfmachinery.rrproducts.com/>