

# Alloy Hollow Side-Eject Tine - .750MT x 5.750L x .570OD



R108-9164



#### **Details**

Manufactured from special high-carbon alloy tubular steel with a precision machined slot in the side wall to allow for more efficient core removal in heavy soils. R&R's unique method of machining maintains the maximum side wall height for strength to avoid bending. These tines are through hardened to RC45-48 to create a much tougher and more wear-resistant tine.

### **Replaces**

Toro 108-9164

#### **Specifications**

Manufacturer R&R Products

A - Tine Type Alloy Hollow Side-Eject

B - Tine Mounting .750 in (19mm)

Dia.

C - Tine Length 5.75 in (146mm) D - Tine Tip Outside .570 in (14.5mm)

(Hole) Dia.

E - Tine Tip Inside

.400 in (10.2mm)

(Core) Dia.

F - Tine Wall

.058 in (1.5mm)

**Thickness** 

#### **Fits Models**

Toro Fairway Aerator

Toro ProCore 1298

Toro ProCore 440

Toro ProCore 648

Toro ProCore 660

Toro ProCore 864

Toro ProCore 880

Toro ProCore 648s

## **TURF MACHINERY SPARES LTD**

3a Monument Way West Woking, GU21 5EN

https://turfmachinery.rrproducts.com/