





Details

Manufactured from special high-carbon alloy tubular steel with a precision machined slot in the side wall to allow for more efficient core removal in heavy soils. R&R's unique method of machining maintains the maximum side wall height for strength to avoid bending. These tines are through hardened to RC45-48 to create a much tougher and more wear-resistant tine. A carbide tip is then added for even longer life. The advantage of using carbide-tipped tines is the ability to maintain your maximum aerating depth consistently over the life of the tines.

Replaces

R&R Products Toro R108-9170 108-9170

Specifications

ManufacturerR&R PrA - Tine TypeAlloy Fwith CaB - Tine Mounting.750 inDia..750 inC - Tine Length4.75 inCarbide TipCarbidD - Tine Tip Outside.425 in(Hole) Dia..275 inE - Tine Tip Inside.275 in(Core) Dia..072 inF - Tine Wall.072 in

R&R Products Alloy Hollow Side-Eject with Carbide Tip .750 in (19mm)

4.75 in (121mm) Carbide Tip .425 in (10.7mm)

.275 in (7mm)

.072 in (1.8mm)

Fits Models Jacobsen GA-24

TURF MACHINERY SPARES LTD

3a Monument Way West Woking, GU21 5EN 01483 764467

https://turfmachinery.rrproducts.com/





Ryan Greensaire II Toro Greens Aerator Toro ProCore 1298 Toro ProCore 440 Toro ProCore 648 Toro ProCore 660 Toro ProCore 864 Toro ProCore 880 Toro ProCore 648s

TURF MACHINERY SPARES LTD

3a Monument Way West Woking, GU21 5EN 01483 764467 https://turfmachinery.rrproducts.com/