



Alloy Hollow Side-Eject Tine with Carbide Tip - .750MT x 6.500L x .525OD

R201515



Details

Manufactured from special high-carbon alloy tubular steel with a precision machined slot in the side wall to allow for more efficient core removal in heavy soils. R&R's unique method of machining maintains the maximum side wall height for strength to avoid bending. These tines are through hardened to RC45-48 to create a much tougher and more wear-resistant tine. A carbide tip is then added for even longer life. The advantage of using carbide-tipped tines is the ability to maintain your maximum aerating depth consistently over the life of the tines.

Replaces

Toro 108-9182

Specifications

Manufacturer	R&R Products
A - Tine Type	Alloy Hollow Side-Eject with Carbide Tip
B - Tine Mounting Dia.	.750 in (19mm)
C - Tine Length	6.5 in (165mm)
Carbide Tip	Carbide Tip
D - Tine Tip Outside (Hole) Dia.	.525 in (13.3mm)
E - Tine Tip Inside (Core) Dia.	.350 in (8.9 mm)
F - Tine Wall Thickness	.072 in (1.8mm)

Fits Models

Toro ProCore 1298
Toro ProCore 440

TURF MACHINERY SPARES LTD

3a Monument Way West Woking, GU21 5EN
01483 764467

<https://turfmachinery.rrproducts.com/>



Alloy Hollow Side-Eject Tine with Carbide Tip - .750MT x 6.500L x .525OD

R201515



Toro ProCore 648
Toro ProCore 660
Toro ProCore 864
Toro ProCore 880
Toro ProCore 648s

TURF MACHINERY SPARES LTD

3a Monument Way West Woking, GU21 5EN
01483 764467

<https://turfmachinery.rrproducts.com/>