



# Alloy Machined Side-Eject Tine - .750MT x 5.500L x .450OD R201535



## Details

Alloy Machined Side-Eject tines remove a soil core which quickly exits the side of the tine through a precision machined slot. This slot is designed to avoid "plugging" that can occur using hollow tubular tines (especially the smaller diameters) in heavy soil conditions. R&R manufactures a wide selection of these side-eject tines machined from special high-carbon alloy steel solid bar and heat treated to RC45-48 in our own heat treating facility. Very popular for the multiple tine holders which fit all greens aerators.

## Specifications

|                                  |                           |
|----------------------------------|---------------------------|
| Manufacturer                     | R&R Products              |
| A - Tine Type                    | Alloy Machined Side-Eject |
| B - Tine Mounting Dia.           | .750 in (19mm)            |
| C - Tine Length                  | 5.500 in (140mm)          |
| D - Tine Tip Outside (Hole) Dia. | .450 in (11.4mm)          |
| E - Tine Tip Inside (Core) Dia.  | .300 in (7.6mm)           |
| F - Tine Wall Thickness          | .065 in (1.7mm)           |

## Fits Models

John Deere Aercore 1000  
John Deere Aercore 1500  
John Deere Aercore 2000  
John Deere Aercore 800  
Ryan GA30  
Toro ProCore 1298  
Toro ProCore 440  
Toro ProCore 648

## TURF MACHINERY SPARES LTD

3a Monument Way West Woking, GU21 5EN  
01483 764467

<https://turfmachinery.rrproducts.com/>



**Alloy Machined Side-Eject Tine - .750MT  
x 5.500L x .450OD  
R201535**



Toro ProCore 660  
Toro ProCore 864  
Toro ProCore 880  
Toro ProCore 648s

**TURF MACHINERY SPARES LTD**

3a Monument Way West Woking, GU21 5EN  
01483 764467

<https://turfmachinery.rrproducts.com/>