



Alloy Hollow Side-Eject Tine - .750MT x 4.750L x .515OD R201641



Details

Manufactured from special high-carbon alloy tubular steel with a precision machined slot in the side wall to allow for more efficient core removal in heavy soils. R&R's unique method of machining maintains the maximum side wall height for strength to avoid bending. These tines are through hardened to RC45-48 to create a much tougher and more wear-resistant tine.

Specifications

| | |
|-------------------------------------|-------------------------|
| Manufacturer | R&R Products |
| A - Tine Type | Alloy Hollow Side-Eject |
| B - Tine Mounting Dia. | .750 in (19mm) |
| C - Tine Length | 4.75 in (121mm) |
| D - Tine Tip Outside (Hole) Dia. | .515 in (13.1mm) |
| E - Tine Tip Inside (Core) Dia. | .300 in (7.6mm) |
| F - Tine Wall Thickness | .072 in (1.8mm) |

Fits Models

- Toro Greens Aerator
- Toro ProCore 1298
- Toro ProCore 440
- Toro ProCore 648
- Toro ProCore 660
- Toro ProCore 864
- Toro ProCore 880
- Toro ProCore 648s

TURF MACHINERY SPARES LTD

3a Monument Way West Woking, GU21 5EN
01483 764467

<https://turfmachinery.rrproducts.com/>